

Pin SpotTR

13W track mounted LED pinspot



Pin SpotTR LED is a true LED replacement for a traditional **Pin Spot**. Featuring both the beam and output characteristics of the original, the **Pin SpotTR** is able to be used in all the same applications.

MAIN FEATURES

- High power LED source and parabolic reflector delivering a tight, bright beam
- Available in both Tungsten and Daylight colour temperature versions
- Remove heat, dimmers and lamp changes in one go

VERSIONS

| Code | CCT | CRI | Lumen |
|--------------------|---------|-------|--------|
| PINSPOTTRTU | 2.800 K | 90 Ra | 755 lm |
| PINSPOTTRDY | 6.100 K | 80 Ra | 978 lm |

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 13W high-power white LED
- CCT: (TU) 2.800 K - (DY) 6.100K
- Luminous flux: (TU) 775 lm - (DY) 978lm
- Lux: (TU) 5'030 lux - (DY) 6'320lx @3 m
- CRI: (TU) 90 - (DY) 80
- Source life expectancy: > 30.000 h

OPTICS

- Beam angle: 6°
- Field angle: 12°

DYNAMIC EFFECTS

- Static mode: selection of static dimmer
- Manual mode: manual adjustment of dimmer and strobe
- Auto mode: built-in programs with execution speed adjustment

BODY

- Body: sturdy die-cast aluminium body
- Body colour: white

ELECTRONICS

- Dimmer: linear 0 ~ 100%, manual knob dimmer
- Operating temperature: -10° ~ +45°

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 18,9W
- Max power consumption (at 120V): 19,6W

PHYSICAL

- Cooling: passive cooling and fan-free
- Suspension and fixing: track-adaptor included for suspension and fixing
- Power connection: track adaptor (EUTRAC, STAFF, GLOBAL, IVELA, Eurostandard Plus compatible)
- IP rating: 30
- Dimensions (WxHxD): 209x167x238mm
- Weight: 1,8kg

ACCESSORIES & RELATED PRODUCTS

- PINSPOTPGWH White filter frame kit for PINSPOT projectors